

Tuff-Red

Part No.: TRD

Colour: Clear With Red Spiral

Construction: Translucent Clear Polyurethane

Reinforcement: Red Poly coated Sprig Wire Helix

Size Available: 2" - 18"

(Larger sizes upon Request)

Temperature: -30°C +120°C

Low | Med | High

Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness

Construction

Use:

Manufactured with an Ester based Polyurethane compound is an excellent alternate to abrasaflex with more attributes including dry-food grade, anti-static and will suit many dry food applications including transferring flour, sugar and other dry food powders



Specifications

Part Number	Nominal Dia.		Min. Bend Radius	Coil Length
	Inches	I.D (mm)		
TFD-51	2"	51	102	10
TFD-57	2 1/4"	57	114	10
TFD-63	2 1/2"	63	126	10
TFD-76	3"	76	152	10
TFD-89	3 1/2"	89	178	10
TFD-102	4"	102	204	10
TFD-114	4 1/2"	114	228	10
TFD-127	5"	127	254	10
TFD-152	6"	152	304	10
TFD-178	7"	178	356	10
TFD-203	8"	203	406	10
TFD-229	9"	229	458	10
TFD-254	10"	254	508	10
TFD-305	12"	305	610	10
TFD-356	14"	356	712	5
TFD-406	16"	406	812	5
TFD-457	18"	457	914	5

Applications

