

Rubber Hose - Steam

STEAM STAR R /210°C ISO6134 2B

Part No.: IH-RS-18

Colour: Red

Tube: Black, smooth, EPM rubber compound

Cover: Red, smooth, pin pricked, cloth impression EPM rubber compound, abrasion, oil, ozone and weather resistant

Reinforcement: High tensile strength steel reinforcements

Size Available: TBC

Temperature: -40°C +210°C picchi 232°C

Low | Med | High

Flexibility

Cycle Life

Pressure Rating


Chemical Resistance

Wall Thickness

Construction

Use:

Delivery hose for high pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry. Oil resistant cover



Standards

ISO 6134

Specifications

Part Number	Size	Internal Diameter	Outside Diameter	Min. Bend Radius	Max. Working Pressure		Min. Burst Pressure	
	inch	mm	mm	mm	bar	PSI	bar	PSI
IH-RS-18-12	1/2"	13	25	120	18	270	180	2700
IH-RS-18-15	5/8"	16	30	155	18	270	180	2700
IH-RS-18-20	3/4"	19	33	185	18	270	180	2700
IH-RS-18-25	1"	25	40	240	18	270	180	2700
IH-RS-18-32	1 1/4"	32	48	330	18	270	180	2700
IH-RS-18-38	1 1/2"	38	54	390	18	270	180	2700
IH-RS-18-50	2"	51	69	520	18	270	180	2700
IH-RS-18-65	2 1/2"	63	81	640	18	270	180	2700
IH-RS-18-75	3"	76	94	745	18	270	180	2700
IH-RS-18-100	4"	102	122	990	18	270	180	2700

Applications

