

Rubber Hose - Steam

Xtreme Steel Steam

Part No.: IH-RSS

Colour: Black

Tube: Black smooth EPDM heat resistant rubber

Cover: Red smooth EPDM heat resistant rubber

Reinforcement: Plies of steel wire cord

Size Available: 13mm - 51mm

Temperature: -40°C +236°C

Low | Med | High

Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness

Construction

Use:

Mandrel-built, high-pressure, wire-braided steam hose designed for service with saturated steam at a maximum pressure of 12BAR (250psi). Not recommended for use on steam cleaners.



Specifications

Part Number	Nominal Dia.		Working Pressure		Weight
	I.D (mm)	O.D (mm)	Bar	kPa	Kg/M
IH-RSS-13	13	25	17	1700	0.53
IH-RSS-19	19	32	17	1700	0.68
IH-RSS-25	25	39	17	1700	0.90
IH-RSS-32	32	46	17	1700	1.30
IH-RSS-38	38	54	17	1700	1.60
IH-RSS-51	51	67	17	1700	2.20

Safety Warning:

Exposure to steam is dangerous. If not properly controlled, steam can cause damage to property, serious injury and even death. You must select the proper steam hose for the given application. Also appropriate installation, usage and maintenance of the steam hose you select will contribute to increasing operator safety.

Applications

