

Rubber Hose - Water

Water Suction

Part No.: IH-RWS

Colour: Black

Tube: Black smooth synthetic rubber

Cover: Black smooth synthetic rubber, abrasion and weather resistant

Reinforcement: Braided synthetic cord incorporating a steel wire helix

Size Available: 19mm - 305mm

Temperature: -20°C +80°C

Low | Med | High

Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness

Construction

Use:

A medium-duty suction hose suitable for use in agricultural, construction and mining industries. The hose is suitable for water, sea water and light slurry in both negative and positive pressure applications.



Specifications

Part Number	Nominal Dia.		Working Pressure		Weight
	I.D (mm)	O.D (mm)	Bar	kPa	Kg/M
IH-RWS-19	19	31	10	1000	-
IH-RWS-25	25	36	10	1000	0.76
IH-RWS-32	32	43	10	1000	0.92
IH-RWS-38	38	49	10	1000	1.20
IH-RWS-44	44	56	10	1000	1.48
IH-RWS-51	51	63	10	1000	1.79
IH-RWS-57	57	70	10	1000	1.90
IH-RWS-64	64	77	10	1000	2.27
IH-RWS-76	76	89	10	1000	2.65
IH-RWS-89	89	102	10	1000	3.50
IH-RWS-102	102	118	10	1000	5.10
IH-RWS-114	114	132	10	1000	6.50
IH-RWS-127	127	146	10	1000	8.10
IH-RWS-152	152	170	5	500	9.30
IH-RWS-204	204	223	5	500	14.60
IH-RWS-254	254	282	5	500	19.20
IH-RWS-305	305	335	5	500	25.60

Applications

