

Rubber Hose - Mining

Contractors Suction

Part No: IH-RWCS

Colour: Black

Tube: Black smooth synthetic rubber.

Cover: Black corrugated synthetic rubber, abrasion and weather resistant.

Reinforcement: Plies of high strength synthetic cord incorporating a steel wire helix.

Size Available: 76mm - 305mm

Temperature: -35°C +70°C

	Low Med High
Flexibility	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>
Cycle Life	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>
Pressure Rating	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/>
Chemical Resistance	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/>
Wall Thickness	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>

Construction

Use:

Highly flexible corrugated rubber hose suitable for the transfer of water in negative pressure applications. Lengths incorporate cuffed ends for ease of inserting hose fitting.



Specifications

Part Number	Nominal Dia.		Working Pressure		Weight
	I.D (mm)	O.D (mm)	Bar	kPa	Kg/M
IH-RWCS-76	76	95	10	1000	3.52
IH-RWCS-102	102	123	10	1000	4.59
IH-RWCS-152	152	176	10	1000	7.86
IH-RWCS-204	204	240	10	1000	11.70
IH-RWCS-254	254	290	10	1000	16.70
IH-RWCS-305	305	-	10	1000	-

Applications

