

Rubber Hose - Hydraulic

SAE 100 R6

Part No.: IH-RR6

Colour: Black

Tube: Synthetic oil resistant rubber.

Cover: Synthetic rubber - abrasion, ozone and weather resistant.

Reinforcement: 1 textile braid.

Size Available: 1/4" - 1"

Temperature: -40°C +120°C

	Low Med High
Flexibility	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>
Cycle Life	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>
Pressure Rating	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>
Chemical Resistance	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/>
Wall Thickness	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/>

Construction

Use:

Low pressure hydraulic oils, air and water.



Standards:

EN 854

Specifications

Part Number	Size	Nominal Dia.		Max. Working Pressure		Min. Burst Pressure		Bend Radius
	inch	I.D (mm)	O.D (mm)	Bar	kPa	Bar	kPa	mm
IH-RR6-04	1/4"	6.4	12.7	28	2800	110	11000	64
IH-RR6-05	5/16"	7.9	14.3	28	2800	110	11000	76
IH-RR6-06	3/8"	9.5	15.9	28	2800	110	11000	76
IH-RR6-08	1/2"	12.7	19.8	28	2800	110	11000	102
IH-RR6-10	5/8"	15.9	23	24	2400	97	9700	127
IH-RR6-12	3/4"	19.0	26	21	2100	83	8300	152
IH-RR6-16	1"	25.4	32.5	13	1300	52	5200	230

Applications



1 2 3 4 5 6 7 8 9 10

RUBBER & COMPOSITE HOSE