



PTFE HOSE

PTFE Hose - SS1SCT

Encapsulated PTFE SS1 Metallic Hose

Part No.: SS1SCT

Construction: Smoothbore PTFE / Convuluted Metallic Hose

Profile: Low Flexibility / Low Pressure

Tube Available: PTFE Virgin / Anti-static Inner Tube

Braid Available: 304 / 316 Stainless Steel

Size Available: 1/2" - 6"

Temperature: -70°C to 260°C

Sintered/Permeation: Slow Sintered (medium level of permeation)

Low | Med | High

Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness

Construction

Use:

The PTFE Smoothbore Liner is extruded within the metallic hose assembly and encapsulated over the flange or fitting, creating a total hygienic seal. The most hygienic PTFE on the market. Approved for food, chemical, cosmetic and pharmaceutical applications.

Standards:

FDA Approved, Accepted by the U.S. Coast Guard, PTFE Perfluorocarbon Resins meets FDA 21 CFR 177.1550



Specifications

Temperature Correction Factor													
-60	-40	-20	0	20	50	100	120	150	180	200	220	250	260
1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.93	0.93	.85	0.85	0.77	0.77	0.70

Part Number	Size inch	Outside Diameter mm	Min. Bend Radius	Working Pressure		Burst Pressure	
				kPa	Bar	kPa	Bar
SS1SCT-12	1/2"	18.00	LIMITED FLEXIBILITY	6500	300	30000	300
SS1SCT-20	3/4"	28.00		5000	200	20000	200
SS1SCT-25	1"	33.70		4400	176	17600	176
SS1SCT-32	1 1/4"	42.60		3500	140	14000	140
SS1SCT-40	1 1/2"	50.90		2800	112	11200	112
SS1SCT-50	2"	61.70		2000	80	8000	80
SS1SCT-65	2 1/2"	85.30		1800	72	7200	72
SS1SCT-80	3"	100.30		1800	72	7200	72
SS1SCT-100	4"	126.30		1600	64	6400	64
SS1SCT-125	5"	155.30		1400	14	5600	56
SS1SCT-150	6"	180.30		1200	12	4800	48

Applications

