

Rubber Hose - Offshore

Petrol/Oil Bunkering Hose

Colour: Black

Tube: Black, smooth, NBR rubber compound

Cover: Black, smooth cloth impression, CR rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

Reinforcement: High strength synthetic plies, with steel wire spirals and 2 crossing copper wires for hose grounding

Size Available: 3" - 300"

Temperature: -30°C +100°C

	Low	Med	High
Flexibility			
Cycle Life			
Pressure Rating			
Chemical Resistance			
Wall Thickness			

Construction

Use:

Suction and delivery hose for crude oil and mixed fuels with aromatic contents up to 50%, offshore operations

Standards:

BS1435: 1987 S15/UNI EN 1765:99 S15



Specifications

Part Number	Size	Internal Diameter	Outside Diameter	Max. Working Pressure		Min. Burst Pressure		Bend Radius	Vacuum
	inch	mm	mm	bar	PSI	bar	PSI	mm	Bar
IH-BUNKER-OIL-HW20-100	4	102	122	20	300	80	1200	630	0.9
IH-BUNKER-OIL-HW20-125	5	127	150	20	300	80	1200	760	0.9
IH-BUNKER-OIL-HW20-150	6	152	180	20	300	800	1200	1050	0.7
IH-BUNKER-OIL-HW20-200	8	203	237	20	300	60	900	1420	0.7
IH-BUNKER-OIL-HW20-250	10	254	290	20	300	60	900	1780	0.5
IH-BUNKER-OIL-HW20-300	12	302	344	20	300	60	900	2115	0.5

Applications

