

### Flexflow

**Part No.:** FFD

**Colour:** Black

**Construction:** Neoprene Rubber Coated Polyester Fabric

**Reinforcement:** Spring Wire Helix

**Size Available:** 1 1/2" - 12"

(Larger sizes upon Request)

**Temperature:** -30°C +120°C

Low | Med | High

Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness

### Construction

**Use:**

Flexflow is constructed from neoprene rubber coated polyester fabric and reinforced with a spring wire helix. Recommended for heavy duty applications.



### Specifications

Part Number	Nominal Dia.		Min. Bend Radius	Coil Length
	Inches	I.D (mm)		
FFD-39	1 1/2"	39	80	10
FFD-51	2"	51	102	10
FFD-57	2 1/4"	57	114	10
FFD-63	2 1/2"	63	126	10
FFD-76	3"	76	152	10
FFD-83	3 1/4"	83	166	10
FFD-89	3 1/2"	89	178	10
FFD-102	4"	102	204	10
FFD-114	4 1/2"	114	228	10
FFD-127	5"	127	254	10
FFD-152	6"	152	304	10
FFD-178	7"	178	356	5
FFD-203	8"	203	406	5
FFD-229	9"	229	458	5
FFD-254	10"	254	508	5
FFD-280	11"	280	560	5
FFD-305	12"	305	610	5

### Applications

