

## Rubber Hose - Chemical

### FRAS Suction

**Part No.:** IH-RFS

**Colour:** Black

**Tube:** FRAS black smooth synthetic rubber, oil mist resistant

**Cover:** FRAS black smooth synthetic rubber, abrasion and weather resistant

**Reinforcement:** Plies of high strength synthetic cord incorporating a steel wire helix.

**Size Available:** 25mm - 102mm

**Temperature:** -35°C +70°C

|                     | Low                                                                                 | Med                                                                                 | High                                                                                |
|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Flexibility         |  |  |  |
| Cycle Life          |  |  |  |
| Pressure Rating     |  |  |  |
| Chemical Resistance |  |  |  |
| Wall Thickness      |  |  |  |

### Construction

#### Use:

Built to AS2660 Class B. This heavy-duty, fire-resistant, anti-static suction hose is ideally suited for use in high fire risk industries.



### Specifications

| Part Number | Nominal Dia. |          | Working Pressure |      | Weight |
|-------------|--------------|----------|------------------|------|--------|
|             | I.D (mm)     | O.D (mm) | Bar              | kPa  | Kg/M   |
| IH-RFS-25   | 25           | 36       | 10               | 1000 | -      |
| IH-RFS-51   | 51           | 65       | 10               | 1000 | 2.10   |
| IH-RFS-76   | 76           | 91       | 10               | 1000 | 3.27   |
| IH-RFS-102  | 102          | 118      | 10               | 1000 | 5.18   |

### Applications

