

Rubber Hose - Chemical

FRAS Delivery

Part No.: IH-RFD

Colour: Black

Tube: FRAS black smooth synthetic rubber, oil mist resistant

Cover: FRAS black smooth synthetic rubber, abrasion and weather resistant

Reinforcement: Plies of high strength synthetic cord

Size Available: 12mm - 102mm

Temperature: -35°C +70°C

	Low	Med	High
Flexibility			
Cycle Life			
Pressure Rating			
Chemical Resistance			
Wall Thickness			

Construction

Use:

Built to AS2660 Class B, this heavy-duty, fire-resistant, anti-static air hose is ideally suited for use in the coal mining industry and other high fire risk areas.



Specifications

Part Number	Nominal Dia.		Working Pressure		Weight
	I.D (mm)	O.D (mm)	Bar	kPa	Kg/M
IH-RFD-12	12	23	20	2000	0.37
IH-RFD-19	19	31	20	2000	0.63
IH-RFD-25	25	37	20	2000	0.78
IH-RFD-32	32	46	20	2000	-
IH-RFD-38	38	52	20	2000	1.20
IH-RFD-51	51	67	20	2000	2.21
IH-RFD-64	64	81	20	2000	3.37
IH-RFD-76	76	92	20	2000	4.15
IH-RFD-102	102	122	20	2000	5.50

Applications

