



Easyflex Convoluted PTFE

Sintered/Permeation: Slow Sintered (medium level of permeation)

Low | Med | High


Flexibility

Cycle Life

Pressure Rating

Chemical Resistance

Wall Thickness



Construction

Use:

General purpose convoluted PTFE hose, convolutions self cleaning spiral construction. Applications include food transfer, chemical dosing, oil, hydraulics and water treatment.



Standards:

USP Class VI compliance PTFE resin used in tubing,
FDA Approved, Accepted by the U.S. Coast Guard,
PTFE Perfluorocarbon Resins meets FDA 21 CFR 177.1550

Specifications

Temperature Correction Factor													
-60	-40	-20	0	20	50	100	120	150	180	200	220	250	260
1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.93	0.93	.85	0.85	0.77	0.77	0.70

Part Number		Size	Internal Diameter (mm)		Wall Thickness	Outside Diameter (mm)		Min. Bend Radius	Standard Max. Working Pressure		Min. Burst Pressure	
316 Braid	304 Braid	Inch	Min.	Max.	mm	Min.	Max.	mm	kPa	Bar	kPa	Bar
ECTB6S-10	ECTB4S-10	3/8"	9.14	9.91	0.76	14.73	15.75	20.30	13800	138	41400	414
ECTB6S-12	ECTB4S-12	1/2"	12.45	13.21	0.89	18.29	19.30	25.40	10300	103	31000	310
ECTB6S-15	ECTB4S-15	5/8"	15.37	16.38	0.89	21.59	22.61	50.80	8300	83	24800	248
ECTB6S-20	ECTB4S-20	3/4"	18.54	19.56	0.89	24.00	25.27	63.50	6900	69	20700	207
ECTB6S-22	ECTB4S-22	7/8"	21.84	22.86	0.89	27.94	29.46	76.20	5700	57	17200	172
ECTB6S-25	ECTB4S-25	1"	24.89	26.16	1.02	32.13	33.66	88.90	4600	46	13800	138
ECTB6S-32	ECTB4S-32	1 1/4"	31.00	33.00	1.02	39.00	42.00	127.00	3400	34	10300	103
ECTB6S-38	ECTB4S-38	1 1/2"	37.50	40.50	1.02	46.99	49.20	152.40	3000	30	9000	90
ECTB6S-50	ECTB4S-50	2"	48.00	52.00	1.02	58.67	59.70	190.50	2300	23	6900	69

Applications

