

Rubber Hose - Mining

Sand & Shot Blast Suction/Discharge Hose

Colour: Black

Tube: NR/BR blend Super Abrasion Resistant (S A R) Rubber

Cover: NR/BR blend Super Abrasion Resistant (S A R) Rubber

Reinforcement: Spiral Synthetic Fabric

Size Available: 1/2" - 3"

Temperature: -30°C +70°C

	Low	Med	High
Flexibility	○	●	○
Cycle Life	○	○	●
Pressure Rating	○	○	●
Chemical Resistance	○	●	○
Wall Thickness	○	●	○

Construction

Use:

Used for suction or discharge of water and light slurry



Specifications

	Size		Max. Working Pressure		Weight Kg/m
	inch	O.D (mm)	PSI	kPa	
IH-SSB-12	1/2"	33	150	1034	0.98
IH-SB-20	3/4"	40	150	1034	1.23
IH-SSB-25	1"	48	150	1034	1.72
IH-SSB-32	1 1/4"	55	150	1034	2.06
IH-SSB-28	1 1/2"	61	150	1034	2.29
IH-SSB-50	2"	76	150	1034	3.14
IH-SSB-80	3"	103	150	1034	4.62

End Connections



Beaded (Rotating) Flanges



Fixed Flanges



Double Flanges



Spigot Flanges

Applications

