

Rubber Hose - Offshore

FUEL AND OIL SD/16 EN 1360 Type 2

Part No.: IH-RFUELSD-16-%

Colour: Black

Tube: Black, smooth, antistatic NBR1 rubber compound.

Cover: Black, smooth, fire proof and antistatic cloth impression CR rubber compound, resistant to chemical products, ozone and weather.

Reinforcement: High strength synthetic plies, with steel spirals and 2 crossing copper wires for hose grounding.

Size Available: Various

Temperature: -30°C +70°C

	Low	Med	High
Flexibility			
Cycle Life			
Pressure Rating			
Chemical Resistance			
Wall Thickness			

Construction

Use:

Suction and delivery hose for fuels and petroleum derivatives with aromatic contents up to 50%



Standards

BS EN 1360

Specifications

Part Number	Size	Internal Diameter	Outside Diameter	Min. Bend Radius	Max. Working Pressure		Min. Burst Pressure		Vacuum
	inch	mm	mm	mm	bar	PSI	bar	PSI	mm hg
IH-RSD-FUEL-16-19	3/4"	19	30	100	16	240	48	720	0.9
IH-RSD-FUEL-16-25	1"	25	38	150	16	240	48	720	0.9
IH-RSD-FUEL-16-32	1 1/4"	32	45	175	16	240	48	720	0.9
IH-RSD-FUEL-16-35	1 3/8"	35	48	190	16	240	48	720	0.9
IH-RSD-FUEL-16-38	1 1/2"	38	51	225	16	240	48	720	0.9
IH-RSD-FUEL-16-40	1 9/16"	40	54	230	16	240	48	720	0.9

Applications

