

Rubber Hose - Hygienic Food Grade

Milk Tanker - Hard Wall

Part No.: IH-RMT

Tube: White NR

Reinforcement: High textile cords with embedded steel helix wire

Cover: Blue NR/EPDM - abrasion, ozone and oil resistant

Size Available: 1" - 4" (Larger sizes upon Request)

Temperature: -40°C +80°C

Safety Factor: 3:1

Low | Med | High

Flexibility ☐ ☐ ☒

Cycle Life ☐ ☐ ☒

Pressure Rating ☐ ☒ ☐

Chemical Resistance ☐ ☐ ☒

Wall Thickness ☐ ☐ ☒

Construction

Use:

Liquid food and suction and delivery.
Special construction for maximum flex-
ibility in milk tanker applications. Sterilize
with 5% soda solution.



Standards:

FDA

Specifications

Part Number	Nominal Dia.			Working Pressure		Min. Bend Radius	Vacuum	Weight Per Mtr
	Inches	I.D (mm)	O.D (mm)	kPa	psi	mm	%	kg.
IH-RMT-25	1"	25	35	1034	150	50	100	0.730
IH-RMT-32	1 1/4"	32	42	1034	150	64	100	0.900
IH-RMT-38	1 1/2"	38	48	1034	150	76	100	1.040
IH-RMT-40	1 9/16"	40	50	1034	150	80	100	1.090
IH-RMT-42	1 5/8"	42	52	1034	150	88	100	1.100
IH-RMT-45	1 3/4"	45	52	1034	150	90	100	1.130
IH-RMT-50	2"	51	61	1034	150	100	100	1.420
IH-RMT-65	2 1/2"	63	75	1034	150	126	100	2.010
IH-RMT-80	3"	76	88	1034	150	228	90	2.590
IH-RMT-100	4"	102	116	1034	150	306	90	3.850